



PART NUMBER	THREAD (MIL-S-8879)	A MAX	B REF	C ± .002	D MIN	E REF	G ± .010	H MAX	J ± .002	K +.005 -0.000	V REF	APPROX WT LBS/100
K3000-06	.1380-32 UNJC-3B	.637	.250	.486	—	.133	.200	.145	.344	.098	.032	.20
K3000-08	.1640-32 UNJC-3B	.637	.250	.486	.168	.149	.200	.215	.344	.098	.032	.24
K3000-3	.1900-32 UNJF-3B	.653	.250	.486	.194	.164	.200	.220	.344	.098	.032	.25
K3000-4	.2500-28 UNJF-3B	.852	.250	.707	.254	.207	.200	.281	.500	.098	.040	.50
K3000-5	.3125-24 UNJF-3B	.914	.322	.707	.317	.253	.230	.328	.500	.130	.050	.77
K3000-6	.3750-24 UNJF-3B	.968	.322	.707	.379	.307	.230	.344	.500	.130	.055	.95
K3000-7	.4375-20 UNJF-3B	1.101	.342	.795	.442	.363	—	.390	.562	.161	.074	1.68

**MATERIAL:** Carbon steel per AMS 5085 (UNS G10500) or alloy steel per AMS 6322 (UNS G8740).

**FINISH:** Cadmium plate per QQ-P-416, Type II, Class 2 and Kaylube molybdenum disulfide dry film lubricant per MIL-L-46010.

**PERFORMANCE:** MIL-N-25027.

**VARIATIONS:** Add "BC" for bottom countersunk rivet holes. Example: K3000-3BC.

K3000

ANCHOR NUT  
CORNER

K3000