



| PART NUMBER | THREAD (MIL-S-8879) | A MAX | C ±.005 | D MIN | H MAX | J ±.002 | K +.005 -.000 | P REF | V REF | W MAX | APPROX WT LBS/100 |
|-------------|---------------------|-------|---------|-------|-------|---------|------------------|-------|-------|-------|-------------------|
| MF5000-04 | .1120-40 UNJC-3B | .651 | .203 | — | .153 | .406 | .098 | .164 | .020 | .315 | .25 |
| MF5000-06 | .1380-32 UNJC-3B | .682 | .220 | — | .171 | .437 | .098 | .190 | .020 | .357 | .25 |
| MF5000-08 | .1640-32 UNJC-3B | .707 | .234 | .168 | .250 | .468 | .098 | .214 | .025 | .367 | .28 |
| MF5000-3 | .1900-32 UNJF-3B | .739 | .250 | .194 | .250 | .500 | .098 | .240 | .025 | .416 | .30 |
| MF5000-4 | .2500-28 UNJF-3B | .801 | .281 | .254 | .281 | .562 | .098 | .300 | .032 | .500 | .49 |
| MF5000-5 | .3125-24 UNJF-3B | 1.010 | .359 | .317 | .328 | .718 | .130 | .375 | .032 | .581 | — |

MATERIAL: C1050 carbon steel per AMS 5085 (UNS G10500).

FINISH: MF500-(*) -Cadmium plate per QQ-P-416, Type II, Class 3 and Kaylube molybdenum disulfide dry lubricant per MIL-L-46010.
 MF500-(*)CW-Cadmium plate per QQ-P-416, Type II, Class 3 and Kaywax.
 MF500(*) -Cadmium plate per QQ-P-416, Type II, Class III.

FLOATABILITY: .030 min. radially from center.

MF5000

ANCHOR NUT
 MINIATURE, FLOATING, TWO-LUG

MF5000