



PART NUMBER	THREAD (MIL-S-8879)	A MAX	B REF	C ±.005	D MIN	E REF	G ±.010	H MAX	J ±.002	K +.005 - .000	V REF	W MAX	APPROX WT LBS/100
K2000-06	.1380-32 UNJC-3B	.935	.215	.344	—	.149	.200	.145	.312	.098	.032	.297	.25
K2000-08	.1640-32 UNJC-3B	.935	.215	.344	.168	.149	.200	.215	.312	.098	.032	.297	.25
K2000-3	.1900-32 UNJF-3B	.950	.215	.344	.194	.164	.200	.220	.312	.098	.032	.328	.30
K2000-4	.2500-28 UNJF-3B	.993	.215	.344	.254	.207	.200	.281	.312	.098	.040	.414	.50
K2000-5	.3125-24 UNJF-3B	1.210	.265	.500	.317	.253	.230	.328	.312	.130	.050	.505	.91
K2000-6	.3750-24 UNJF-3B	1.284	.265	.500	.379	.307	.230	.344	.312	.130	.055	.614	1.06

**MATERIAL:** C1050 carbon steel per AMS 5085 (UNS G10500).

**FINISH:** Cadmium plate per QQ-P-416, Type II, Class 2 and Kaylube molybdenum disulfide dry film lubricant per MIL-L-46010.

**PERFORMANCE:** MIL-N-25027.

**VARIATIONS:** Add "BC" for bottom countersunk rivet holes. Example: K2000-3BC.

**K2000**

**ANCHOR NUT  
ONE-LUG**

**K2000**